


Innovative solutions for controlling mechanical movement

MANAGING MOTION

UTILIZING HELI-CAL® FLEXURE TECHNOLOGY



Helical Products Company, Inc.

CONTENTS

THE HELI-CAL FLEXURE

Now You Can Dream.....	3
The HELI-CAL Flexure Problem Solver	4
Design Benefits of the Flexure	6
Operating Characteristics	6

HELI-CAL FLEXURE FLEXIBLE COUPLINGS


HELI-CAL Flexure, Basic Product Summary	9
W Series, Aluminum and Stainless Steel	10
DS Series, Aluminum	12
MC Series, Aluminum and Stainless Steel	14
A Series, Aluminum	16
H Series, Stainless Steel.....	16
Special Bore Configurations	18
PF Series, Aluminum and Stainless Steel	20

IDEA STIMULATORS

X-Series Radial Slot Coupling	21
A New Angle on Universal Joints	22
Flexure Attachments that Make Sense	23
What is a Machined Spring?	24

PLUS

Engineering Proposal Form	25
Literature Request Form.....	26
Philosophy	27
Representation	back cover



Often imitated, never duplicated.

HELI-CAL® Flexure, flexible couplings are machined from single piece, homogenous high-strength materials into helical (curved beam) configurations which eliminate elastomeric elements like rubber bushings, spiders, rubber discs and pads. Helical couplings compensate for shaft misalignment and work at high speed, transmitting high torque at a constant velocity. There is zero backlash. No maintenance is needed.

Helical couplings provide dynamic stability and vibration-free, smooth bearing loads, even at misaligned positions. Helical couplings find applications in petrochemical plants, instrumentation, encoders, lead screws, ball screws, air cooling units, pumps, machine tools, CNC machines, duplicators, computer peripherals, wind power generators, anywhere there is a need for managing motion.

Six reasons why you should buy HELICAL

State-of-the-art, single piece, flexible (and torsionally stiff) couplings, utilizing the HELI-CAL Flexure.

- ♦ No maintenance, no backlash, no lubrication, constant velocity, and smooth bearing loads.

Engineering collaboration

- ♦ Technical consultation (free).

Quality product

- ♦ Fifty years experience in perfecting manufacturing machinery and procedures used to produce HELI-CAL Flexure couplings that are of consistent high quality.

Service/on time shipping

- ♦ We do what we say we'll do e.g.- if we say, shipment in five working days we mean shipment in five working days.

Originator of HELI-CAL Flexure couplings

- ♦ Over 10,000 successful coupling designs; over 30,000 customers served.

Total product offerings

- ♦ In addition to a full line of standard couplings, the HELI-CAL Flexure can accommodate a variety of design requirements, such as special/customized end attachments like tangs, clamps, flanges or threaded ends.



Helical Products Company, Inc.
901 West McCoy Lane
P.O. Box 1069
Santa Maria, CA 93456-1069 USA
Toll Free 877-353-9873
Fax 805-928-2369


Now You Can Dream . . .

The inspiration for the HELI-CAL Flexure, the cylindrical helix ingredient for our basic Helical product lines, came from the observation that one piece, "flexured" flexible couplings offered maximum versatility in terms of form, function and reliability.

Over time, the adaptability of the HELI-CAL Flexure has helped to solve thousands of mechanical misalignment and motion control problems.

The unique, mechanical characteristics of the "Flexure" have enabled Helical Products Company, Inc. to develop a series of highly versatile, "flexured" products which can compensate for irregularities such as angular and skewed misalignment, parallel offset and axial motion. All of this can be accomplished while maintaining constant rotational velocity and smooth bearing loads.

Here's the HELI-CAL Flexure . . .



The HELI-CAL Flexure is a flexible helix (curved beam) machined from one piece of material into a specific configuration that incorporates special design requirements, performance features and/or characteristics.

Helical's product lines today include miniature flexible couplings, u-joints, machined springs, and power transmission flexible couplings.

The following pages present the many advantages of HELI-CAL Flexure technology. The charts, data and information are based on our "standard" series of one-piece, flexible couplings, which are usable for a multitude of applications. As you become acquainted with the Flexure, you will see how versatile it can be, with for example, specials, machined springs, u-joints, and attachments. You will see also how the HELI-CAL Flexure can have a positive and marked impact on system performance, production efficiencies and overall cost savings.

If you do not see it here, just contact us. Our application engineers can design, develop and produce a custom HELI-CAL Flexure to meet your specific requirements. **H**

Coil Width

By varying the thickness of the coils, a Flexure can accommodate increasing amounts of torque and radial loads. The designer may specify torsional stiffness and compression spring rates independent of other factors.

Connecting Dreams with Design Solutions: The HELI-CAL Flexure Problem Solver

Freedom of design... for maximum versatility

The Helical hallmark is flexibility in form and function. Designed from the start with your goals in mind and manufactured to exacting specifications, the HELI-CAL Flexure offers many problem-solving, performance-enhancing features.

Coil configuration

The individual performance capability of each Flexure is determined by: coil width, inside diameter, number of coils, number of starts and material. Altering any one of these factors changes the performance characteristics of the "Flexure."

For example, the HELI-CAL Flexures illustrated display identical outside diameters and lengths. The effects of their variable characteristics—such as coil width, inside diameter, number of coils and starts are explained in the adjacent pictures.

Coil widths and inside diameters

As the coil width or inside diameter are changed such aspects as *torque...angular misalignment (bending moment)... parallel offset (radial load)... torsional stiffness... and compression spring rate*, are altered.

Inside Diameter

When the inside diameter changes, so does the torque capacity, torsional stiffness and axial spring rates, without restricting your choice of bore sizes.

Number of coils

As the number of coils is changed, all of the characteristics except the torque capacity are affected.

Number of coil starts

- 1) A single start design has one continuous coil.
- 2) A double start has a second coil starting 180 degrees from the first.
- 3) A triple start has three interwound coils, each spaced 120 degrees apart.

When a multi-start helix is used (double or triple), the effect is to increase the torque capacity and torsional stiffness while reducing misalignment capabilities (angular and parallel).

Material

The proper material used in the manufacture of any HELI-CAL Flexure affects much more than just torque capacity. Factors such as elasticity, fatigue, corrosion resistance, mass, magnetic permeability, operating temperature, availability and cost also play important roles. High strength materials such as 17-4PH CRES*, 15-5 PH, C300, BETA C Titanium and 7075-T6 Aluminum, are just a few of the common choices for meeting design and performance needs.

*CRES - Corrosion resistant steel

Number of Coils



When the number of coils is changed the torque capability remains unaffected. All of the other characteristics change.

Number of Coil Starts



Multiple, (typically two) helical beams provide high torsional stiffness. Shown: single, double and triple start.

Attachments

In addition to being able to alter the characteristics of the HELI-CAL Flexure, you may have your attachment method integrated into the final product.

Typical attachment options might include:

- integral clamps
- set screws
- set screw at one end and an integral clamp at the other
- pins
- slotted hubs
- flanges
- gears
- removable caps
- threaded bores with a wrench flat
- or . . . whatever your design requires

Bore variety

Helical Flexures may be engineered to include a variety of bore configurations. These variations include round, threaded, single or double-D, spline, keyway, tapered or ... it's your choice!

The HELI-CAL Flexure or flexible coil section of the coupling can be custom designed and manufactured to your specifications. Whether your considerations include high torque, angular or parallel misalignment, critical torsional stiffness, precise compression spring rates, or special end connections, chances are excellent that the HELI-CAL Flexure will meet or exceed your particular design requirements. **H**

The HELI-CAL Flexure, Basic Product Summary,
(page 9), summarizes our basic series of
HELI-CAL Flexure couplings. By referring to
various charts and coupling descriptions, you
will see how you can select a product that
meets your design parameters.
(See pages 10-21 for product specifics)

For more information or engineering assistance,
please contact us.

Angular

Design Benefits of the Flexure

More than a coupling

The HELI-CAL Flexure concept brings enormous design flexibility to your applications. Depending on your needs, the Flexure can serve as a flexible shaft coupling, universal joint, spring clutch, machined spring or your own unique specialized component.

Adaptability

The Flexure's ability to accommodate various performance characteristics and Helical's ability to integrate attachments directly enhances your freedom to design.

One-piece integrity

Not only does the Flexure integrate multiple functions and parts into a single compact unit—no moving parts, no maintenance and no backlash—it can incorporate complex attachments.

State-of-the-art

High quality performance is achieved with magnetic or non-magnetic corrosion-resistant stainless steel, as well as aluminum alloys. Flexures are also successfully manufactured using various materials such as Delrin™ and titanium.

Operating Characteristics

Misalignment compensation

The flexing capacity of the HELI-CAL Flexure can compensate for a variety of misalignments, including parallel, angular and skewed (three-dimensional) misalignment. The Flexure solutions for these misalignment situations are shown in the adjacent photographs.



Angular misalignment is the easiest form of misalignment for most couplings to accept, and thus one of the most practical applications of a flexible coupling. Allowing only enough space between coils to partially close the gap during bending, the HELI-CAL Flexure can accept an angular misalignment of 20 degrees or more (and even up to 90 degrees in special u-joint applications).


Optimized torque capacity

The basic requirement of a flexible coupling is to transmit torque loads without permanent distortion or damage and without imposing undue bending or radial loads upon the driver or driven components. Once the working torque rating of a HELI-CAL Flexure coupling is established—based on misalignment and design criteria, material specifications and service factors supplied during the design process—its operational life is virtually unlimited.

Configurable torsional stiffness

Every flexible shaft coupling has some torsional flexibility. Torsional flexibility reflects the amount of twist in a system; torsional stiffness the degree of resistance against twist. The HELI-CAL Flexure can be configured (with thicker coils, for example), to provide the exact amount of torsional flexibility required in an application.

Parallel



Skewed



Parallel misalignment is the most difficult form of misalignment for couplings to compensate for. It can also be the most damaging to shafts, bearings and motors. The HELI-CAL Flexure, through lateral displacement, transforms an application's parallel misalignment problems into angular displacement within the coupling. The center coils of the HELI-CAL Flexure can become an intermediate shaft that can allow 10, 20 or 30 thousandths of an inch of parallel offset or more.

Smooth bearing loads

Bearing loads are primarily generated by a coupling's natural resistance to bending, and can be very destructive forces to an apparatus and its rotational components. The HELI-CAL Flexure maintains a very constant radial and bending load at all points of rotation, providing exceptionally uniform bearing loads.

Constant velocity

In a rotating system, constant velocity refers to the relative rotational speed of the input and output shafts. In a constant velocity system the driven end of the coupling turns exactly the same rate as the driver end. When operating under a uniform load the HELI-CAL Flexure design provides constant velocity and alleviates:

When shafts are not in the same plane (skewed), the HELI-CAL Flexure's abilities to compensate are the same as with either parallel or angular misalignment - but in the third dimension. A Flexure designed with more coils in a series can compensate for as much three-dimensional misalignment as your application requires.

- ◆ Backlash: the HELI-CAL Flexure has zero backlash, because of its one-piece construction.
- ◆ Angular misalignment, which can induce large fluctuations in rotational velocity in many coupling designs, is corrected by the HELI-CAL Flexure's constant spring rate at all points of rotation.
- ◆ Torsional variations, which can induce differences in hub-to-hub velocity when subjected to dynamic loading, are minimal in steady-state applications of the HELI-CAL Flexure.
- ◆ Concentricity, when there is a lack of it—particularly in the case of couplings with backlash or where production variation is difficult to prevent—the HELI-CAL Flexure's one-piece integrity minimizes sinusoidal variations.

Continued -



This sampling of "standard" HELI-CAL Flexure couplings and specialized u-joints illustrates the variety of materials, coil configurations, bore diameters and attachment methods available to you.

No matter what its size or shape, the HELI-CAL Flexure design assures performance, reliability, quality and versatility, arguably unmatched in the coupling industry.

Adaptable Operating Speeds

The ability to adapt to high—and low—speed applications is another inherent benefit of the HELI-CAL Flexure's design. The Flexure transmits motion throughout its length and cross section in a continuous helix from end to end. Torsional loading tends to make the HELI-CAL Flexure draw toward its centerline, reducing the chance of whipping action normally associated with rotating components. Consequently, vibrations are kept to a minimum at all rotating points.

Axial Compensation

Axial movement is inherent in any rotating componentry, such as the rotor assembly in a motor. Through compression/extension, the HELI-CAL Flexure absorbs and compensates for axial movement or end play. The curved-beam structure of the HELI-CAL Flexure operates naturally in this axial compensation mode, and special designs can accommodate for even large displacement applications. ■

HELI-CAL Flexure, Basic Product Summary

Refer to the summary chart on the next page to get an idea as to which coupling series most closely fits your application needs. You'll then be able to find the appropriate coupling by following the series column down to the page number. If you do not see the coupling you need in these pages, let us know. Our engineers can create special Flexure designs to meet your particular performance demands.

The charts on the following pages highlight features and technical data for each of the standard HELI-CAL coupling series.

Information covered by each chart includes:

- ♦ Dimensional data ♦ Special notes
- ♦ Performance data ♦ Ordering information

HELI-CAL Flexure, Basic Product Summary

W Series		DS Series	MC Series		A Series	H Series
aluminum 7075-T6	stainless steel 17-4PH	aluminum 7075-T6	aluminum 7075-T6	stainless steel 17-4PH	aluminum 7075-T6	stainless steel 17-4PH
						
Description						
General purpose, light to medium duty. An economical, maintenance free coupling with metric dimensions, used in a variety of applications.	Stainless steel version of the "WA(C)" series, with higher torque capacity and torsional stiffness. Increased fatigue resistance with metric dimensions and fasteners.	Low inertia, high performance, aluminum coupling, using Helical double start technology. Torsionally stiffer and higher torque capacity than the "A" series. Lighter with lower inertia than the "H" series.	A general purpose aluminum coupling, used where more parallel misalignment is required. Has a large range of shaft sizes, with optional keyways.	Stainless steel version of "MCA(C)" series, with higher torque capacity and torsional stiffness. Increased fatigue resistance.	General purpose, light to medium duty. An economical, maintenance free coupling, used in a variety of applications.	Stainless steel version of "A" series, with higher torque capacity and torsional stiffness. Increased fatigue resistance.
Typical applications						
Used for encoder/resolver applications, low torque pump, lead screw and various other applications.	For situations requiring a heavy duty coupling, for pump, lead screws, and positioning systems. Also for process equipment in industrial situations. Anywhere a rugged, tough, long-lasting coupling is needed.	For high speed motion control systems, where fast response time is important. E.g., lead and ball screws, encoders/resolvers, and anywhere high torsional stiffness is required.	Good for encoder/resolver applications, moderate torque pump, lead screw, and various other applications.	Good for pump, conveyor systems, and industrial processing equipment, where absolute reliability is required. Anywhere a rugged, tough, long-lasting coupling is needed.	Used for encoder/resolver applications, low torque pump, lead screw and various other applications.	For situations requiring a heavy duty coupling such as pumps, lead screws, and positioning systems; also for process equipment in industrial situations. Anywhere a rugged, tough, long-lasting coupling is needed.
Misalignment compensation						
5° angular, .25mm parallel offset, .25mm axial motion	5° angular, .25mm parallel offset, .25mm axial motion	3° angular, .010 inch parallel offset, .008 inch axial motion	5° angular, .030 inch parallel offset, .010 inch axial motion	5° angular, .030 inch parallel offset, .010 inch axial motion	5° angular, .010 inch parallel offset, .010 inch axial motion	5° angular, .010 inch parallel offset, .010 inch axial motion
Torque range						
.59-20 Nm	1.2-39 Nm	12-234 lbin	20-286 lbin	40-556 lbin	1.2-51 lbin	2.4-100 lbin
Standard bores (inch and/or metric bores available in all couplings)						
0.118-0.787 inch 3mm-20mm	0.118-0.787 inch 3mm-20mm	0.188-0.750 inch 4.78-19.05mm	0.250-875 inch 6.35-22.23mm	0.250-1.000 inch 6.35-25.40mm	0.059-0.750 inch 1.5-19.05mm	0.059-0.750 inch 1.5-19.05mm
Attachment						
Clamp or set screw	Clamp or set screw	Clamp	Clamp or set screw Keyways optional	Clamp or set screw Keyways optional	Clamp or set screw	Clamp or set screw
Operating temperatures						
Up to 100° C	Up to 300° C	Up to 200° F	Up to 200° F	Up to 600° F	Up to 200° F	Up to 600° F
Speed (in wind-up direction)						
10,000 rpm	10,000 rpm	10,000 rpm	3,600 rpm	3,600 rpm	10,000 rpm	10,000 rpm
For more information, see page						
10	10	12	14	14	16	16

Note: For PF Series see page 20.

Features



W SERIES
(aluminum shown)


- Metric dimensions and fasteners
- Metric and/or inch bores available
- Available in 7075-T6 aluminum alloy or 17-4 PH corrosion-resistant steel
- General purpose

If you are working in the *metric* world, the W Series is for you. It combines the best features of the A Series and the H Series, with the


convenience of metric dimensions and fasteners for your metric based designs. The W Series can be used in a wide range of applications from driving components with light torque requirements, such as encoders and tachometers (aluminum), to lead screws and pumps requiring greater torque (stainless steel).

Attachment Methods

Integral Clamp / WAC & W7C




Set Screw / WA & W7 (two each end @ 120°)




Internal Configuration

Relief *

Major and minor diameter shafts may enter flexure area during operation



Unequal diameter shafts



Equal diameter shafts


* Dark areas indicate relief within the coupling interior

How To Order

Coupling part numbers consist of four sections. To determine the correct numbers/letters for each section of a specific coupling part number, please refer to the charts on the following pages.

Example

- 1 Basic Model Number**
(W = metric, A = aluminum, C = integral clamp)



** Refer to "Standard Bore Diameters" section of chart

- 1 Basic Model Number:**
Choose material and attachment method.

WAC = Aluminum, Integral Clamp

WA = Aluminum, Set Screw

W7C = Stainless Steel, Integral Clamp

W7 = Stainless Steel, Set Screw

- 2 Outside Diameter Designator:** This two-digit number represents the coupling outside diameter. Based on the Performance Data in the middle of the chart, select the Outside Diameter Designator by moving left to the appropriate diameter.

- 3 Major Bore Designator:** The larger of the two bores, its diameter is expressed in either millimeters (6mm) or in 32nds of an inch (-8 equals 1/4 inch). Please review your selection to determine if both bores can be made in the size coupling you have selected in **2**. **It is important that the larger bore be stated first.**

- 4 Minor Bore Designator:** The smaller of the two bores is expressed the same as the Major Bore Designator. **Either bore can be mm or inch.** Please specify mm when metric.

HELICAL W SERIES, Aluminum, Technical Data

① Basic Model Number			② Dimensional Information		③ Standard Bore Diameters		④ Performance Data		Inertia	Attachment Screw		
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter	L Length (mm)	(+0.05mm/-0.00mm) Note 5	Momentary Dynamic Torque Note 2 (Nm)	Torsional Rate (degree/Nm)	x 10 ⁻⁴ (kgcmsec ²) Note 6	Integral Clamp	Screw Size	Seating Torque	Center Line
WAC	WA	15	15mm	22	3.00 4.00 5.00	3mm 4mm 5mm	0.71 0.66 0.59	5.1 7.2 10.0	0.028	M2x.4	0.5	2.5
				20					0.025		M3x.5	1.0
WAC	WA	20	20mm	28	4.00 5.00 6.00	4mm 5mm 6mm	1.3 1.2 1.1	2.7 3.5 4.5	0.11	M3x.5	2.0	3.8
				20					0.079		M3x.5	1.0
WAC	WA	25	25mm	30	6.00 7.00 8.00 9.00 10.00	6mm 7mm 8mm 9mm 10mm	2.9 2.8 2.6 2.4 2.2	1.5 1.8 2.2 2.8 3.5	0.30	M3x.5	2.0	3.8
				24					0.24		M4x.7	2.1
WAC	WA	30	30mm	38	9.00 10.00 11.00 12.00	9mm 10mm 11mm 12mm	4.9 4.6 4.3 4.0	1.1 1.3 1.6 1.9	0.78	M4x.7	4.7	5.0
				30					0.60		M5x.8	4.7
WAC	WA	40	40mm	50	12.00 13.00 14.00 15.00 16.00	12mm 13mm 14mm 15mm 16mm	12 11 11 10 9.7	0.45 0.51 0.59 0.67 0.78	3.3	M5x.8	9.5	5.8
				50					3.3		M6x1	7.7
WAC	WA	50	50mm	54	14.00 16.00 18.00 19.00 20.00	14mm 16mm 18mm 19mm 20mm	19 18 17 16 15	0.25 0.31 0.39 0.43 0.49	7.6	M6x1	16	6.7
				54					7.6		M6x1	7.7

HELICAL W SERIES, Stainless Steel, Technical Data

① Basic Model Number			② Dimensional Information		③ Standard Bore Diameters		④ Performance Data		Inertia	Attachment Screw		
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter	L Length (mm)	(+0.05mm/-0.00mm) Note 5	Momentary Dynamic Torque Note 2 (Nm)	Torsional Rate (degree/Nm)	x 10 ⁻⁴ (kgcmsec ²) Note 6	Integral Clamp	Screw Size	Seating Torque	Center Line
W7C	W7	15	15mm	22	3.00 4.00 5.00	3mm 4mm 5mm	1.4 1.3 1.2	1.9 2.6 3.7	0.078	M2x.4	0.5	2.5
				20					0.070		M3x.5	1.0
W7C	W7	20	20mm	28	4.00 5.00 6.00	4mm 5mm 6mm	2.6 2.5 2.3	0.99 1.3 1.6	0.32	M3x.5	2.0	3.8
				20					0.22		M3x.5	1.0
W7C	W7	25	25mm	30	6.00 7.00 8.00 9.00 10.00	6mm 7mm 8mm 9mm 10mm	5.7 5.5 5.1 4.7 4.3	0.54 0.66 0.82 1.0 1.3	0.84	M3x.5	2.0	3.8
				24					0.66		M4x.7	2.1
W7C	W7	30	30mm	38	9.00 10.00 11.00 12.00	9mm 10mm 11mm 12mm	9.5 8.9 8.3 7.7	0.40 0.48 0.58 0.70	2.2	M4x.7	4.7	5.0
				30					1.7		M5x.8	4.7
W7C	W7	40	40mm	50	12.00 13.00 14.00 15.00 16.00	12mm 13mm 14mm 15mm 16mm	23 22 21 20 19	0.16 0.19 0.21 0.24 0.28	9.2	M5x.8	9.5	5.8
				50					9.2		M6x1	7.7
W7C	W7	50	50mm	54	14.00 16.00 18.00 19.00 20.00	14mm 16mm 18mm 19mm 20mm	37 35 33 31 30	0.092 0.11 0.14 0.16 0.18	21	M6x1	16	6.7
				54					21		M6x1	7.7

Conversions
1mm = .039 inch
1Nm = 8.85 lbin
1deg/Nm = .113 deg/lbin

Notes

- Shaft misalignments:
 Angular 5 degrees
 Parallel Offset .25 mm (.50 mm T.I.R.)
 Axial Motion ± .25 mm
- Dynamic torque ratings are momentary values. For non-reversing applications, divide by 2. Divide by 4 for reversing applications. Should the torque ratings be marginal for your application, contact us for analysis.
- Material : 7075-T6 aluminum alloy
 Finish: clear anodize
 or Material: 17-4 PH high-strength stainless steel.
 Finish: natural
- Manufacturing dimensional tolerances unless otherwise specified are:
 x ± .5 mm
 $x.x$ ± .25 mm
- Please refer to page 19 for other available bore dimensions.
- Inertia is based on smallest standard bore diameter.
- Keyways available on the 40 mm and 50 mm OD only.

Features



DS SERIES

- High torsional stiffness
- Low radial loads
- Parallel misalignment capability
- Low inertia


The DS Series was designed for today's high performance motion control systems. This Series incorporates two helical beams (double start) in each of two separate HELI-CAL Flexures (double flexure), combining greater end-to-end rotational accuracy with radial flexibility in one design.

Available only with integral clamp attachments, the DS Series provides the high torsional stiffness and low inertia necessary for positioning devices, servo motors and lead screws.

The DS Series also provides you with substantial .010-inch parallel offset capability, reducing the need for high-precision alignment during assembly operations. It's your ticket to greater system accuracy and reliability. Available only in 7075-T6 aluminum.

Attachment Methods


Integral Clamp / DSAC




Internal Configuration

Relief *

Major and minor diameter shafts may enter flexure area during operation



Unequal diameter shafts



Equal diameter shafts

* Dark areas indicate relief within the coupling interior

How To Order

Coupling part numbers consist of four sections. To determine the correct numbers/letters for each section of a specific coupling part number, please refer to the charts on the following pages.

Example

① Basic Model Number

(DS = double start, A = aluminum, C = integral clamp)

② Outside Diameter Designator

DSAC 125 - 16 - 12

④ Minor Bore Designator **

③ Major Bore Designator **

① Basic Model Number:

DSAC = Double start flexure,
Aluminum and Integral Clamp

② Outside Diameter Designator:

This three-digit number represents the coupling outside diameter. Based on the Performance Data in the middle of the chart, select the Outside Diameter Designator by moving left to the appropriate diameter.

③ Major Bore Designator:

The larger of the two bores, its diameter is expressed in either 32nds of an inch (-8 equals 1/4 inch) or in millimeters (6mm). Please review your selection to determine if both bores can be made in the size coupling you have selected in ②. It is important that the larger bore be stated first.

④ Minor Bore Designator:

The smaller of the two bores is expressed the same as the Major Bore Designator. Either bore can be inch or mm.

** Refer to "Standard Bore Diameters" section of chart

HELICAL DS SERIES, Aluminum, Technical Data

①		②		③ & ④		Attachment Screw					
Basic Model Number		Dimensional Information		Standard Bore Diameters		Performance Data		Inertia	Screw Size	Seating Torque	Center Line
Integral Clamp Attachment	Outside Diameter Designator	D Outside Diameter (in.)	L Length (in.)	(+.002in/-0.000in) Note 6 Size in. & (mm) Bore Designator (1/32 in.)	Momentary Dynamic Torque Note 2 (lbin) Torsional Rate (degree/lbin)	x 10 ⁻⁴ (lbinsec ²) Note 7	Integral Clamp Note 4 (lbin)	(in.)			
DSAC	075	3/4	1.25	0.188 (4.78) 0.250 (6.35)	6 8	14 12	0.30 0.40	0.091	4-40	10	.12
DSAC	100	1	1.50	0.250 (6.35) 0.313 (7.95) 0.375 (9.53)	8 10 12	31 29 25	0.13 0.16 0.19	0.35	6-32	19	.15
DSAC	125	1 1/4	1.75	0.313 (7.95) 0.375 (9.53) 0.500(12.70) 0.625(15.88)	10 12 16* 20*	61 58 47 35	0.062 0.080 0.12 0.19	0.98	10-24	50	.22
DSAC	150	1 1/2	2.25	0.375 (9.53) 0.500(12.70) 0.625(15.88)	12 16 20	130 115 94	0.030 0.042 0.062	2.7	10-24	50	.22
DSAC	200	2	2.50	0.500(12.70) 0.625(15.88) 0.750(19.05)	16 20 24	234 215 190	0.016 0.020 0.026	9.5	1/4-20	120	.26

* Refer to note 8

Notes

- Shaft misalignments:

Angular	3 degrees
Parallel Offset	.010 in. (.020 in. T.I.R.)
Axial Motion	± .008 in.
- Dynamic torque ratings are momentary values. For non-reversing applications, divide by 2. Divide by 4 for reversing applications. Should the torque ratings

- be marginal for your application, contact us for analysis.
- Material : 7075-T6 aluminum alloy
Finish: clear anodize
- Metric fasteners available on request.
- Manufacturing dimensional tolerances unless otherwise specified are:

fraction	± 1/64
x.xx	± .01 in.
- Please refer to page 18 for other available bore dimensions.
- Inertia is based on smallest standard bore diameter.
- This bore size requires an operating clearance diameter greater than coupling outside diameter.

Features



MC SERIES
(aluminum shown)

- Industrial motor shaft couplings
- Large parallel misalignment capacity
- High torque capacity
- Large shaft diameters
- Keyways available


This versatile series of couplings provides you with a full range of torque capacities and bore sizes, all with 1/32-inch parallel misalignment capability. These couplings attach to shafts with your choice of integral

clamps or set screws. Combine this with optional keyways and the MC Series is tailor-made for your application.

From medium-duty (aluminum) to heavy-duty (stainless steel), this series provides solutions for a wide range of applications. From pumps and lead screws to conveyors, chances are an MC Series coupling will fit your needs. Available in 7075-T6 aluminum alloy or 17-4 PH corrosion resistant steel (CRES).


Attachment Methods

Integral Clamp / MCAC & MC7C



Set Screw / MCA & MC7


(two each end @ 120°)




Internal Configuration

Relief *

Major and minor diameter shafts may enter flexure area during operation



Unequal diameter shafts



Equal diameter shafts

* Dark areas indicate relief within the coupling interior

How To Order

Coupling part numbers consist of four sections. To determine the correct numbers/letters for each section of a specific coupling part number, please refer to the charts on the following pages.

Example

① Basic Model Number

(MC = motor coupling, A = aluminum, C = integral clamp)

② Outside Diameter Designator

MCAC 150 - 16 - 12

④ Minor Bore Designator **

③ Major Bore Designator **

① Basic Model Number:

Choose material and attachment method.

MCAC = Aluminum, Integral Clamp

MCA = Aluminum, Set Screw

MC7C = Stainless Steel, Integral Clamp

MC7 = Stainless Steel, Set Screw

② Outside Diameter Designator:

This three-digit number represents the coupling outside diameter. Based on the Performance Data in the middle of the chart, select the Outside Diameter Designator by moving left to the appropriate diameter.

③ Major Bore Designator:

The larger of the two bores, its diameter is expressed in either 32nds of an inch (-8 equals 1/4 inch) or in millimeters (6mm). Please review your selection to determine if both bores can be made in the size coupling you have selected in ②. **It is important that the larger bore be stated first.**

④ Minor Bore Designator:

The smaller of the two bores is expressed the same as the Major Bore Designator. **Either bore can be inch or mm.**

** Refer to "Standard Bore Diameters" section of chart

HELICAL MC SERIES, Aluminum, Technical Data

①			②		③ & ④		Attachment Screw						
Basic Model Number			Dimensional Information		Standard Bore Diameters		Performance Data		Inertia	Screw Size		Seating Torque	Center Line
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	L Length (in.)	(+.002in/-0.000in) Note 6 Size in. & (mm) Bore Designator (1/32 in.)	Momentary Dynamic Torque Note 2 (lb/in)	Torsional Rate (degree/lbin)	x 10 ⁻⁴ (lb/insec ²) Note 7	Integral Clamp Note 4	Set Screw Note 4	(lbin)		(in.)
MCAC		100	1	1.75	0.250 (6.35) 0.313 (7.95) 0.375 (9.53)	8 10 12	26 23 20	0.270 0.370 0.530	0.41	6-32		19	.15
											10-24	25	.15
MCAC		125	1 1/4	2.37	0.313 (7.95) 0.375 (9.53) 0.500 (12.70)	10 12 16*	51 47 38	0.130 0.170 0.300	1.3	10-24		50	.22
											1/4-20	65	.20
MCAC		150	1 1/2	2.62	0.375 (9.53) 0.500 (12.70)	12 16	100 88	0.065 0.100	3.1	10-24		50	.22
											1/4-20	65	.20
MCAC		200	2	3.00	0.500 (12.70) 0.625 (15.88)	16 20	178 164	0.035 0.049	11.4	1/4-20		120	.26
											1/4-20	65	.30
MCAC		225	2 1/4	3.50	0.625 (15.88) 0.750 (19.05) 0.875 (22.23)	20 24 28	286 262 233	0.024 0.032 0.044	21.5	1/4-20		120	.26
											1/4-20	65	.40

* Refer to note 8

HELICAL MC SERIES, Stainless Steel, Technical Data

①			②		③ & ④		Attachment Screw						
Basic Model Number			Dimensional Information		Standard Bore Diameters		Performance Data		Inertia	Screw Size		Seating Torque	Center Line
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	L Length (in.)	(+.002in/-0.000in) Note 6 Size in. & (mm) Bore Designator (1/32 in.)	Momentary Dynamic Torque Note 2 (lb/in)	Torsional Rate (degree/lbin)	x 10 ⁻⁴ (lb/insec ²) Note 7	Integral Clamp Note 4	Set Screw Note 4	(lbin)		(in.)
MC7C		100	1	1.75	0.250 (6.35) 0.313 (7.95) 0.375 (9.53)	8 10 12	51 46 40	0.098 0.140 0.190	1.1	6-32		19	.15
											10-32	25	.15
MC7C		125	1 1/4	2.37	0.313 (7.95) 0.375 (9.53) 0.500 (12.70) 0.625 (15.88)	10 12 16* 20*	98 91 74 54	0.048 0.062 0.110 0.210	3.8	10-32		56	.22
											1/4-28	65	.20
MC7C		150	1 1/2	2.62	0.375 (9.53) 0.500 (12.70) 0.625 (15.88)	12 16 20	194 170 140	0.024 0.037 0.060	8.7	10-32		56	.22
											1/4-28	65	.20
MC7C		200	2	3.00	0.500 (12.70) 0.625 (15.88) 0.750 (19.05)	16 20 24	347 319 282	0.013 0.018 0.025	31.9	1/4-28		135	.26
											1/4-28	65	.30
MC7C		225	2 1/4	3.50	0.625 (15.88) 0.750 (19.05) 0.875 (22.23) 1.000 (25.40)	20 24 28 32	556 510 454 392	0.009 0.012 0.016 0.023	60.0	1/4-28		135	.26
											1/4-28	65	.40

* Refer to note 8

Notes

- Shaft misalignments:
Angular 5 degrees
Parallel Offset .030 in. (.060 in. T.I.R.)
Axial Motion ± .010 in.
- Dynamic torque ratings are momentary values. For non-reversing applications, divide by 2. Divide by 4 for reversing applications. Should the torque ratings be marginal for your application, contact us for analysis.

- Material : 7075-T6 aluminum alloy
Finish: clear anodize
or Material: 17-4 PH high-strength stainless steel.
Finish: natural
- Metric fasteners available on request.
- Manufacturing dimensional tolerances unless otherwise specified are:
fraction ± 1/64
XXX ± .01 in.
- Please refer to page 19 for other available bore dimensions.
- Inertia is based on smallest standard bore diameter.
- With integral clamp attachments only, this bore size requires an operating clearance diameter greater than coupling outside diameter.
- Inch and metric keyways available.



A SERIES




H SERIES

Attachment Methods

Integral Clamp / ACR & HCR



Set Screw / AR & HR (two each end @ 120°)



Features, A Series

- Light to medium duty
- Non-magnetic
- Economical
- No maintenance

The A Series coupling meets performance demands over a wide range of applications, including drive systems for encoders, instrumentation, lead screws, small pumps, feed rollers and anywhere a light to medium duty, torsionally flexible coupling is required.

Features, H Series

- High torque capacity
- High fatigue resistance
- Corrosion resistant steel (CRES)

The H Series coupling is ideal when high strength, excellent fatigue resistance and high torsional stiffness is called for in your application. The H Series' premium performance capability is designed for applications requiring a heavy-duty coupling, such as drive systems, small pumps and gear boxes.

Shared Features of the A & H Series


- No maintenance
- Shaft sizes from 3/32 to 3/4

An array of options, in a variety of diameter sizes, allows you to tailor the A or H Series to your specific applications. A and H Series options include set screw or integral clamp attachments and inch or metric bores.


Internal Configuration

Relief *

Major and minor diameter shafts may enter flexure area during operation



Unequal diameter shafts



Equal diameter shafts

* Dark areas indicate relief within the coupling interior

How To Order

Coupling part numbers consist of four sections. To determine the correct numbers/letters for each section of a specific coupling part number, please refer to the charts on the following pages.

Example

① Basic Model Number

(A = aluminum, C = integral clamp, R = internal relief)
(H = Stainless Steel, C = integral clamp, R = internal relief)

② Outside Diameter Designator

ACR 112 - 16 - 12
(HCR)

④ Minor Bore Designator **

③ Major Bore Designator **

① Basic Model Number:

Choose material and attachment method.

ACR = Aluminum, Integral Clamp

AR = Aluminum, Set Screw

HCR = Stainless Steel, Integral Clamp

HR = Stainless Steel, Set Screw

② Outside Diameter Designator:

This three-digit number represents the coupling outside diameter. Based on the Performance Data in the middle of the chart, select the Outside Diameter Designator by moving left to the appropriate diameter.

③ Major Bore Designator:

The larger of the two bores, its diameter is expressed in either 32nds of an inch (-8 equals 1/4 inch) or in millimeters (6mm). Please review your selection to determine if both bores can be made in the size coupling you have selected in ②. **It is important that the larger bore be stated first.**

④ Minor Bore Designator:

The smaller of the two bores is expressed the same as the Major Bore Designator. **Either bore can be inch or mm.**

** Refer to "Standard Bore Diameters" section of chart

HELICAL A SERIES Aluminum, Technical Data

Basic Model Number			Dimensional Information		Standard Bore Diameters		Performance Data		Inertia	Screw Size		Seating Torque	Center Line
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	L Length (in.)	(+.002in/-000in) Note 6 Size in. & (mm)	Bore Designator (1/32 in.)	Momentary Dynamic Torque Note 2 (lb/in)	Torsional Rate (degree/lbin)	x 10 ⁻⁵ (lb/insec ²) Note 7	Integral Clamp Note 4	Set Screw Note 4	(lbin)	(in.)
ACR		050	1/2	0.75	0.094 (2.39) 0.125 (3.18)	3 4	3.7 3.5	0.98 1.3	0.11	1-72		4.0	.09
				0.50					0.069		2-56	1.3	.06
ACR		062	5/8	0.80	0.125 (3.18) 0.157 (3.99) 0.188 (4.78)	4 5 6	7.1 6.7 6.2	0.51 0.66 0.86	0.28	2-56		4.5	.10
				0.62					0.21		4-40	4.3	.07
ACR		075	3/4	0.90	0.125 (3.18) 0.157 (3.99) 0.188 (4.78) 0.250 (6.35)	4 5 6 8	10 10 9.8 8.6	0.29 0.36 0.44 0.68	0.66	4-40		10	.12
				0.75					0.54		6-32	8.0	.09
ACR		087	7/8	1.06	0.188 (4.78) 0.250 (6.35) 0.313 (7.95)	6 8 10*	19 17 15	0.20 0.28 0.41	1.5	6-32		19	.15
				0.87					1.2		6-32	8.0	.10
ACR		100	1	1.25	0.250 (6.35) 0.313 (7.95)	8	27	0.17	3.0	6-32		19	.15
				1.00	0.375 (9.53)	10 12	24 22	0.24 0.33	2.3		10-24	25	.15
ACR		112	1 1/8	1.50	0.250 (6.35) 0.313 (7.95)	8 10	43 40	0.094 0.12	5.6	6-32		19	.15
				1.12	0.375 (9.53) 0.500 (12.70)	12 16	37 28	0.17 0.32	4.1		10-24	25	.14
ACR		125	1 1/4	1.62	0.375 (9.53) 0.500 (12.70)	12 16*	48 39	0.11 0.20	9.3	10-24		50	.22
				1.25	0.625 (15.88)	20*	29	0.37	6.9		1/4-20	65	.16

* Refer to note 8

HELICAL H SERIES Stainless Steel, Technical Data

Basic Model Number			Dimensional Information		Standard Bore Diameters		Performance Data		Inertia	Screw Size		Seating Torque	Center Line
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	L Length (in.)	(+.002in/-000in) Note 6 Size in. & (mm)	Bore Designator (1/32 in.)	Momentary Dynamic Torque Note 2 (lb/in)	Torsional Rate (degree/lbin)	x 10 ⁻⁵ (lb/insec ²) Note 7	Integral Clamp Note 4	Set Screw Note 4	(lbin)	(in.)
HCR		050	1/2	0.75	0.094 (2.39) 0.125 (3.18)	3 4	7.5 7.0	0.36 0.48	0.31	1-72		4.0	.09
				0.50					0.19		2-56	1.3	.06
HCR		062	5/8	0.80	0.125 (3.18) 0.157 (3.99) 0.188 (4.78)	4 5 6	14 13 12	0.19 0.24 0.31	0.78	2-56		4.5	.10
				0.62					0.58		4-40	4.3	.07
HCR		075	3/4	0.90	0.125 (3.18) 0.157 (3.99) 0.188 (4.78) 0.250 (6.35)	4 5 6 8	21 20 20 17	0.11 0.13 0.16 0.25	1.8	4-40		10	.12
				0.75					1.5		6-32	8.0	.09
HCR		087	7/8	1.06	0.188 (4.78) 0.250 (6.35) 0.313 (7.95)	6 8 10*	37 34 30	0.072 0.10 0.15	4.1	6-32		19	.15
				0.87					3.3		6-32	8.0	.10
HCR		100	1	1.25	0.250 (6.35) 0.313 (7.95)	8 10	52 47	0.062 0.086	8.3	6-32		19	.15
				1.00	0.375 (9.53)	12	42	0.12	6.5		10-32	25	.15
HCR		112	1 1/8	1.50	0.250 (6.35) 0.313 (7.95)	8 10	83 78	0.035 0.045	15.6	6-32		19	.15
				1.12	0.375 (9.53) 0.500 (12.70)	12 16	71 55	0.061 0.12	11.3		10-32	25	.14
HCR		125	1 1/4	1.62	0.375 (9.53) 0.500 (12.70)	12 16*	94 77	0.041 0.071	26.0	10-32		56	.22
				1.25	0.625 (15.88)	20*	57	0.13	19.4		1/4-28	65	.16

* Refer to note 8

Notes

1. Shaft misalignments:
 Angular 5 degrees
 Parallel Offset .010 in.
 (.020 in. T.I.R.)
 Axial Motion ± .010 in.
2. Dynamic torque ratings are momentary values. For non-reversing applications, divide by 2. Divide by 4 for reversing applications. Should the torque ratings be marginal for your application, contact us for analysis.
3. Material : 7075-T6 aluminum alloy used for ACR / AR series.
 Finish: clear anodize
 or Material: 17-4 PH high-strength stainless steel used for HCR / HR series.
 Finish: natural
4. Metric fasteners available on request.
5. Manufacturing dimensional tolerances unless otherwise specified are:
 fraction ± 1/64
 x.xx ± .01 in.
6. Please refer to page 18 for other available bore dimensions.
7. Inertia is based on smallest standard bore diameter.
8. With integral clamp attachments only, this bore size requires an operating clearance diameter greater than coupling outside diameter.

HELICAL W SERIES / pages 10 – 11

Basic Model Number		Outside Diameter		Special Bore Diameters			
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter	With Relief		Restricted Bore Configurations*	
				Minimum Size mm	Maximum Size mm	Maximum Size mm	Bore Depth mm
W7C/WAC	W7/WA	15	15mm	3.00	5.00	7.30	6.00
				3.00	5.00	9.00	4.85
W7C/WAC	W7/WA	20	20mm	4.00	6.35	9.81	8.55
				4.00	6.35	14.00	4.85
W7C/WAC	W7/WA	25	25mm	6.00	10.00	14.56	8.55
				6.00	10.00	17.00	5.85
W7C/WAC	W7/WA	30	30mm	9.00	12.70	17.30	11.00
				9.00	12.70	20.00	6.85
W7C/WAC	W7/WA	40	40mm	12.00	16.00	24.80	15.50
				12.00	16.00	25.40	17.00
W7C/WAC	W7/WA	50	50mm	14.00	20.00	32.11	15.50
				14.00	20.00	38.10	17.00

HELICAL DS SERIES / pages 12 – 13

Basic Model Number		Outside Diameter		Special Bore Diameters			
Integral Clamp Attachment	Outside Diameter Designator	D Outside Diameter (in.)		With Relief		Restricted Bore Configurations*	
				Minimum Size in. & (mm)	Maximum Size in. & (mm)	Maximum Size in. & (mm)	Bore Depth in. & (mm)
DSAC	075	3/4		0.188 (4.78)	0.250 (6.35)	0.390 (9.90)	0.25 (6.35)
DSAC	100	1		0.250 (6.35)	0.394 (10.00)	0.563 (14.31)	0.38 (9.65)
DSAC	125	1 1/4		0.313 (7.95)	0.630 (16.00)	0.668 (16.98)	0.44 (11.18)
DSAC	150	1 1/2		0.375 (9.53)	0.630 (16.00)	0.908 (23.07)	0.57 (14.48)
DSAC	200	2		0.500 (12.70)	0.750 (19.05)	1.280 (32.50)	0.68 (17.27)

Notes

- 1 Bore sizes are placed into the part number with leading dashes after the basic model number. Standard bore dimensions are noted in 32nds of an inch, such as 8/32 or 3/32 in. The respective dash numbers would be -8 and -3. Any bore dimensions that are not an integer number of 32nds should be converted to their millimeter equivalent with "mm" after the numerical designation, e.g., .315 in = 8 mm.
- 2 When specifying part numbers, metric bore diameters are specified without trailing zeros after the decimal point, e.g. .315 in.

= 8.00 mm, but the bore designation is – 8mm. This is only for simplicity in ordering and does not affect the tolerances of the actual bore dimensions. Bore tolerances are specified on the *Engineering Proposal Form* at the end of the catalog.


- 3 Manufacturing dimensional tolerances unless otherwise specified are:

fract	x.xx	x.xxx	angle
± 1/64	± .010	± .005	± 2°


x	x.x	x.xx	angle
±.5mm	±.25mm	±.15mm	±2°

- 4 A complete line of specialty OEM and end-user products is available; please refer to the *Engineering Proposal Form* and/or contact our Engineering Department.
- 5 A chart showing our standard line of instrumentation couplings with precision bore tolerancing is available upon request.
- 6 All parts are available with metric or inch fasteners to be compatible with the fastener system used in your designs.
- 7 Bore diameters less than minimum listed may be possible for one bore only. Contact our Engineering Department.

*Restricted Bore Configuration



Unequal diameter shafts



Equal diameter shafts

HELICAL MC SERIES / pages 14 – 15

Basic Model Number		Outside Diameter		Special Bore Diameters			
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	With Relief		Restricted Bore Configurations*	
				Minimum Size in. & (mm)	Maximum Size in. & (mm)	Maximum Size in. & (mm)	Bore Depth in. & (mm)
MC7C		100	1	0.156 (3.96)	0.394 (10.00)	0.563 (14.30)	0.37 (9.40)
	MCAC			0.156 (3.96)	0.394 (10.00)	0.563 (14.30)	
	MC7			0.156 (3.96)	0.394 (10.00)	0.630 (16.00)	
	MCA			0.156 (3.96)	0.394 (10.00)	0.630 (16.00)	
MC7C		125	1 ¹ / ₄	0.313 (7.95)	0.630 (16.00)	0.668 (16.98)	0.51 (12.95)
	MCAC			0.313 (7.95)	0.512 (13.00)	0.668 (16.98)	
	MC7			0.313 (7.95)	0.630 (16.00)	0.750 (19.05)	
	MCA			0.313 (7.95)	0.512 (13.00)	0.750 (19.05)	
MC7C		150	1 ¹ / ₂	0.313 (7.95)	0.630 (16.00)	0.908 (23.07)	0.66 (16.76)
	MCAC			0.313 (7.95)	0.512 (13.00)	0.908 (23.07)	
	MC7			0.313 (7.95)	0.630 (16.00)	1.000 (25.40)	
	MCA			0.313 (7.95)	0.512 (13.00)	1.000 (25.40)	
MC7C		200	2	0.375 (9.53)	0.750 (19.05)	1.280 (32.50)	0.75 (19.05)
	MCAC			0.375 (9.53)	0.630 (16.00)	1.280 (32.50)	
	MC7			0.375 (9.53)	0.750 (19.05)	1.500 (38.10)	
	MCA			0.375 (9.53)	0.630 (16.00)	1.500 (38.10)	
MC7C		225	2 ¹ / ₄	0.375 (9.53)	1.000 (25.40)	1.525 (38.73)	0.86 (21.84)
	MCAC			0.375 (9.53)	0.875 (22.23)	1.525 (38.73)	
	MC7			0.375 (9.53)	1.000 (25.40)	1.750 (44.45)	
	MCA			0.375 (9.53)	0.875 (22.23)	1.750 (44.45)	

HELICAL A and H SERIES / pages 16 - 17

Basic Model Number		Outside Diameter		Special Bore Diameters			
Integral Clamp Attachment	Set Screw Attachment	Outside Diameter Designator	D Outside Diameter (in.)	With Relief		Restricted Bore Configurations*	
				Minimum Size in. & (mm)	Maximum Size in. & (mm)	Maximum Size in. & (mm)	Bore Depth in. & (mm)
ACR/HCR		050	1/2	0.090 (2.29)	0.125 (3.18)	0.236 (6.00)	0.19 (4.83)
	AR/HR			0.090 (2.29)	0.125 (3.18)	0.315 (8.00)	0.12 (3.05)
ACR/HCR		062	5/8	0.090 (2.29)	0.197 (5.00)	0.325 (8.26)	0.20 (5.08)
	AR/HR			0.090 (2.29)	0.197 (5.00)	0.375 (9.53)	0.14 (3.56)
ACR/HCR		075	3/4	0.118 (3.00)	0.250 (6.35)	0.390 (9.90)	0.25 (6.35)
	AR/HR			0.118 (3.00)	0.250 (6.35)	0.512 (13.00)	0.18 (4.57)
ACR/HCR		087	7/8	0.138 (3.50)	0.315 (8.00)	0.444 (11.27)	0.31 (7.87)
	AR/HR			0.118 (3.00)	0.315 (8.00)	0.630 (16.00)	0.20 (5.08)
ACR/HCR		100	1	0.156 (3.96)	0.375 (9.53)	0.563 (14.31)	0.31 (7.87)
	AR/HR			0.156 (3.96)	0.375 (9.53)	0.630 (16.00)	0.26 (6.60)
ACR/HCR		112	1 ¹ / ₈	0.188 (4.78)	0.512 (13.00)	0.684 (17.38)	0.45 (11.43)
	AR/HR			0.188 (4.78)	0.512 (13.00)	0.630 (16.00)	0.27 (6.86)
ACR/HCR		125	1 ¹ / ₄	0.313 (7.94)	0.625 (15.88)	0.669 (17.00)	0.51 (12.95)
	AR/HR			0.313 (7.94)	0.625 (15.88)	0.750 (19.05)	0.32 (8.13)



Features

- No maintenance, lubrication or backlash.
- Available in aluminum and stainless steel with 2, 2.5 and 3 inch OD. Standard with quick change tapered bushings.
- Offered in inch or millimeter bore sizes up to 1 3/4 inch diameter.
- Torque capacities up to 1800 lbin.
- High torsional stiffness.
- Compensates for angular, parallel and axial misalignment.
- More torque for less money.

The PF Series incorporates the convenience of interchangeable bushings, providing for quick and easy changes in bore sizes, while using the same HELI-CAL flexible coupling center section. By designing the tapered bushings to hold more torque than the maximum torque capacity of the coupling, the need for keyways has been eliminated.

HELICAL PF Series PowerFlex, Technical Data

STANDARD BORE DIAMETER +.002 / -.000 in (+0.05 / -.00 mm)			PERFORMANCE DATA			PART NUMBER	DIMENSIONAL INFORMATION				ATTACHMENT SCREW			WEIGHT
Max w/RELIEF see note 1 in (mm)	Max w/STEP BORE see note 2 in (mm)	Min in (mm)	Momentary Dynamic Torque see note 3 lbin (Nm)	Torsional Rate deg/lbin (deg/Nm)	Parallel Offset in (mm)		OD in (mm)	L in (mm)	L1 in (mm)	B in (mm)	Size	Qty	Seating Torque lbin (Nm)	lb (kg)
.875 (22.00)	1.000 (25.00)	.500 (12.00)	250 (28)	.027 (.24)	.025 (.65)	PFA200	2.00 (50.8)	4.00 (101.6)	3.12 (79.2)	.82 (20.8)	M5	4	55 (6.2)	0.87 (.39)
			530 (60)	.0096 (.085)	.025 (.65)	PFS200							65 (7.3)	2.31 (1.05)
1.125 (28.00)	1.375 (35.00)	.500 (12.00)	480 (55)	.014 (.12)	.030 (.75)	PFA250	2.50 (63.5)	4.75 (120.7)	3.70 (94.0)	1.00 (25.4)	M6	5	90 (10)	1.68 (.76)
			1,025 (115)	.0050 (.045)	.030 (.75)	PFS250							110 (12)	4.46 (2.02)
1.375 (35.00)	1.750 (44.00)	.625 (16.00)	840 (95)	.0080 (.071)	.035 (.85)	PFA300	3.00 (76.2)	5.50 (139.7)	4.47 (113.5)	1.13 (28.7)	M6	5	90 (10)	2.70 (1.22)
			1,800 (205)	.0030 (.026)	.035 (.85)	PFS300							110 (12)	7.31 (3.32)

Angular: 4 degrees Axial: +/- .020in (.50mm) Max. RPM: 6,000

Conversion from Horsepower to Torque: (HP x 63,000) ÷ RPM = Trq (lbin) or (HP x 7,119) ÷ RPM = Trq (Nm)

Lightly grey shaded boxes indicate stainless steel (CRES)


Note 1 Shaft sizes less than or equal to the Max w/RELIEF can penetrate to the center of the coupling. See drawing.

Note 2 Shaft sizes greater than the Max w/RELIEF up to the Max w/STEP BORE can only penetrate to the B dimension. See drawing.

Note 3 Dynamic torque ratings are momentary values. For non-reversing applications, divide by 2.

Divide by 4 for reversing applications. Should the torque ratings be marginal for your application, contact us for analysis.

M6.0 Hex Head Cap Screw 5 places (M5.0 Hex Head Cap Screw 4 places on PFA/PFS 200)



*Seating of screws: For correct installation, progressively tighten screws to specified torque in sequence shown above.



Features

- Ideal for motion control applications (servo motors).
- Up to 10 times greater torsional stiffness than beam types.
- Low cost alternative to bellows types.
- No moving parts.
- No maintenance.
- No backlash.
- No lubrication.
- Excellent quality.

The X-series couplings offer a cost effective balance between couplings that are too stiff radially and those not stiff enough torsionally for servo-type applications. It features high torsional stiffness, low radial loads, one-piece integrity, good flexibility, and zero backlash. Created for high performance motion control systems, the X-Series incorporates two flexible element sets—combining greater end-to-end rotational accuracy with radial flexibility—in one design.

HELICAL X-Series, Aluminium, Technical Data

Bore Diameter (+.05 / - .00 mm)		Performance Data			Basic Model Number	Dimensional Information		Inertia†	Attachment Metric Cap Screws		Weight
Min (mm)	Max (mm)	Torque Rating (Nm)	Torsional Rate (Deg/Nm)	Parallel Offset (mm)		OD (mm)	L (mm)	X 10 ⁴ (kgcmsec ²)	Size (mm)	Seating Torque (Nm)	Weight (grams)
3.00	6.00	0.30	1.13	0.10	XCA15	15*	24	0.028	M2.50 -.45	1.1	9.2
4.00	8.00	0.50	0.46	0.10	XCA20	20**	28	0.11	M3 -.5	2.0	20
6.00	10.00	1.00	0.22	0.15	XCA25	25	30	0.30	M3 -.5	2.0	33
9.00	12.70	2.00	0.13	0.15	XCA30	30	38	0.78	M4 -.7	4.7	60
10.00	17.00	5.00	.066	0.20	XCA40	40	60	3.9	M5 -.8	9.5	177
12.00	22.23	10.00	.029	0.20	XCA50	50	65	10.5	M6 -1.0	16	306

How To Order

Example

Basic Model Number

(X = cross-slotted coupling, C = integral clamp, A = aluminum, S=303 stainless steel)

Outside Diameter Designator


XCA25 - 10mm - 8

Minor Bore Designator

Major Bore Designator

Metric bores are specified as millimeter size (-10mm).

Inch bores are expressed as number of 32nds (-8 = 8/32 = 1/4" = .250").



Major and minor diameter shafts may enter flexing area during operation.

A New Angle on Universal Joints


HELI-CAL Flexured U-joints Provide Precision Operating Characteristics

A universal joint is a mechanical connection between rotating shafts which are generally not in parallel, but intersecting. "U-joints" transmit torque and motion.

U-joints are used in a variety of applications, wherever handling significant angular misalignment is the main focus. Typical applications include: articulating mechanisms, food processing equipment, replacement for expensive gearboxes, and drives where motor position must be moved angularly off centerline of the driven unit.


The oldest and most common type of u-joint is called the Cardan or Hooke type joint. It consists of hub yokes, connected by a cross shaped intermediate member. These popular u-joints are frequently used in automotive applications. Because the design incorporates several different piece parts, the moving parts of this type of u-joint usually require lubrication; and as the joint wears, the amount of backlash or free play within the joint itself grows. Even a lubricated Cardan u-joint will require periodic maintenance, and may leak lubricant.

Cardan u-joint



Performance wise, Cardan u-joints can transmit relatively high torque with minimal radial loads. But, by design these u-joints have difficulty compensating for parallel offset and axial misalignment. Cardan types also introduce rotational inconsistencies into drive systems, a phenomenon known as "non-constant velocity rotation."


The HELI-CAL Flexure is an advanced and unique u-joint solution that generally exceeds the capabilities of common u-joint designs. A Helical u-joint is really a flexure capable of over 5° of angular misalignment. It may accommodate up to 90° of angular misalignment in certain circumstances. This type of u-joint will also compensate for axial and parallel misalignment.



HELI-CAL Flexure

A frequent application of the Helical flexured u-joint is the direct replacement for a 90° bevel gearbox. Gearboxes are expensive, and usually need lubrication for their meshing gear surfaces and bearings. Replacement with a maintenance free Helical flexured u-joint can save money, both on initial purchase price and on maintenance costs. Flexured u-joints can be beneficial most anywhere—for example: aerospace, appliances, electronics, control mechanisms and drives, medical and optical devices, sewing machines, instrumentation, and textile machinery.

The performance capability of each HELI-CAL Flexure is determined by characteristics such as: flexure outside diameter, inside diameter, coil thickness, material, number of coils, and number of starts. By altering these



Helical flexured u-joints can be made to suit specific specifications and/or requirements. Note coil widths.

characteristics, torque capacity, angular and parallel misalignment capabilities, torsional and lateral bending rates of flexured u-joints can be made to suit specific specifications and/or requirements.

By using a flexured u-joint, the customer benefits from:

- ◆ Choice of materials
- ◆ Infinite choice of end attachments
- ◆ Optimized misalignment and torque capacities
- ◆ A variety of torsional and lateral bending rates
- ◆ Ability to run in either manual or motor-driven applications
- ◆ Constant velocity

An added bonus—flexured u-joints *do not* have:

- ◆ Backlash
- ◆ Moving parts
- ◆ Maintenance and lubrication requirements
- ◆ Limited selection of capabilities and sizes
- ◆ Limited angular misalignment capability

Once the designer/customer provides Helical with the performance requirements for his/her device, machine, or equipment, a specific flexure design that will meet or exceed application requirements is developed. An attachment may also be specified to securely interface with adjacent components. The result is a Helical flexured u-joint that works as an integral part of the customer's application.

Helical flexured u-joints are tailor-made for customer applications, using customers' specific requirements as a starting point. The finished product is a Helical flexured u-joint that "fits like a glove" in the device, machine, or equipment.

Helical Products Company, with its unique HELI-CAL Flexure, covers most u-joint requirements. Whether the application requires just a small angle of slightly more than 5°, or one calling for a 90° bend, Helical has a "flexure" answer. This "answer" employs the infinitely variable HELI-CAL Flexure, with its amazing range of variable characteristics. No longer is it necessary to use a "one size fits all" approach to u-joints. ■

Flexure Attachments That Make Sense

How To Make The Right Connections

For many years Helical Products Company has been recognized as the pioneer in the design and manufacture of helical beam type couplings, universal joints (UJs) and machined springs. The unique capabilities of the HELI-CAL Flexure have solved countless design projects for engineers in many diverse industries.

But curiously, engineers or designers often fail to recognize how important the integration of the flexure /attachment is in improving component performance. Typically, the portion of a coupling that fastens, clamps, meshes or otherwise contacts adjacent components is referred to as an "attachment." It is these various attachments and their potential impact on system design, we will discuss here.

First, let's consider some of the special characteristics inherent to a HELI-CAL Flexure. Flexured couplings and UJs are backlash free and provide constant velocity rotation regardless of misalignment. Any means of attachment used in conjunction with this type of product should maintain these properties, and complement them. The most common form of coupling attachment, set screws, can introduce backlash into a system unintentionally. Having said this, it should be noted that Helical does sell many flexures with set screw attachments.

[The key to assuring this attachment method does not compromise effectiveness of the entire system is knowing the configuration of the adjacent components, D-shafts for example, and the anticipated duty cycle the component will encounter.]

Clamp style attachments are frequently used as a zero backlash, positive means of transmitting rotational motion between components. When compared to set screws on a performance basis, clamps squeeze around the shaft circumference rather than creating a dimple in the shaft. Clamp attachments better lend themselves to applications where the components are assembled and disassembled occasionally. Clamps require more linear space for the coupling, are inherently less dynamically balanced and slightly more expensive to manufacture. At times neither of



The right attachment will reduce assembly/production costs.

these attachment methods may be optimal for your application. This raises the question,

"What other alternatives do I have?"


The variety of attachments available is limited only by the imagination of the design engineer, and the laws of physics. The configuration of coupling attachments can be as simple as the plain bore or as complex as a pinion gear. The purpose in seeking a customized attachment is to minimize the cost, optimize performance, simplify design, reduce system size, or reduce weight.

By using the HELI-CAL Flexure along with an attachment, the engineers are allowed to dream in their system design. Most designers view a special or modified standard with a cost being too great. In actuality, customized attachments more than pay for themselves. The proper attachment will minimize assembly-production time and reduce the total number of parts to purchase, to maintain in inventory, and to assemble. All of this produces an overall production savings.

Pictured are some examples of customized attachments and the benefits they have provided. ■



A threaded shaft attachment offers several advantages. Fine axial length adjustments and blind assembly are just two potential uses.



Detachable caps permit flexure installation where components cannot be spread apart to slide the flexure onto component shafts.



Integrating a lever arm into a clamp attachment flexure allowed linear motion to be converted to rotary motion.



A custom blind attachment designed to transmit torque in a single direction.

What is a Machined Spring?

By Gary L. Boehm
Senior Research Engineer
Helical Products Company, Inc.

Gary Boehm has spent over 30 years in machined spring R&D. Following are questions frequently asked of Gary regarding machined springs, and his answers.

Q: What is a machined spring?

A: A Helical machined spring is a single piece of material machined into a spring configuration. Key to the versatility of the machined spring is the HELI-CAL Flexure, a flexible helix beam concept utilized in the manufacture of Helical machined springs. Because Helical springs are "machined" to specific design requirements, they provide more precise performance, features and functions than can other more traditional types of springs.

Q: What are some of the advantages of machined springs over conventional springs?

A: With machined springs, desired features or functions can be made part of the spring, such as: special attachments, precise spring rates, multiple integral coils, and other special characteristics. These aspects are generally not possible with traditional springs.

Machined springs also support multiple design objectives such as reliability, repeatability, and integration of multiple parts, which results in a reduction of assembly complexity.

Q: How are machined springs different?

A: The ends of machined springs can be made very square, a beneficial feature for compression springs. Attachments for torsional springs can be integrated so that no forces act upon the spring, just the moment enabling torsional deflections. Extension (tension) springs can include robust attachments that are resistant to breakage. Machined springs can provide very precise, linear deflection rates because virtually all residual stresses are eliminated. As a result, there are no internal stresses to overcome before deflection occurs.

Q: Explain the terms "single start" and "multiple starts."

A: A Single start spring is a single continuous coil element which starts at one end and terminates at the other end. This configuration is common to most springs. A "double start" spring has two intertwined continuous coil elements. In effect, this puts two independent helices in the same cylindrical plane. Multiple start flexures, such as triple start etc., are similar extensions of the concept.


Q: What are some of the benefits of multiple start flexures?



A: Multiple start flexures are beneficial because they not only provide redundant elastic elements should a failure occur, but a failed element (coil) will be physically trapped by the remaining one(s).

Another multi-start benefit applies to compression and tension springs. When compressed (or extended), single start springs provide a reaction force plus a moment. This moment is created because the line of action is through the longitudinal centerline of the spring, and the spring force is action at the coil mean centerline. The distance between these centerlines provides the moment arm of the subject moment. On multiple start flexures, all internal moments are resolved within the spring. The big benefit is that these multiple start springs then compress (or extend) in a very straight manner. There is no tendency for the spring to squirm when deflected, and no restraint is necessary to resolve the free moment.

Sometimes there is a desire to have multiple elastic rates in a given spring. For instance, a compression torsion and lateral bending rate may be specified. With most types of springs accomplishing one of these rates can be a challenge, but three is impossible. Not so with a multiple start Helical machined spring. A machined spring designer can choose coil size, number of coils and multiple start coil features to achieve specified, different, elastic rates.



Q: I understand that machined springs can be designed so that the coils don't touch. Does this mean that no sound would be generated by the spring?

A: Exactly. In those applications where resonance is desired for high efficiencies, the best choice is a machined spring of a multiple start configuration. In fact, machined springs may be the only choice under these circumstances. The linear rate and non-contact feature of the machined spring provide outstanding performance. The multiple start aspect prevents lateral bending and lateral translations from compromising in-line motions.

Proposal Form for Couplings and U-Joints (Please refer to the literature request form for machined spring proposal forms.)

Name _____ Telephone _____ E-Mail _____
 Company _____ Fax _____
 Address _____ Street / P.O. Box _____ City _____ State _____ Zip _____

OPERATING INFORMATION**1. DRIVE ***

a or b. DIRECTION

d. REVERSING

c. CONTINUOUS

e. STOP-START _____ cycles/sec

f. RPM _____ g. MANUAL _____

4. TORSIONAL RATE *

deg/lb. in. or deg/Nm

a. less than _____ b. equal to _____ c. greater than _____

2. SERVICE *

a. OPERATING TORQUE _____ lbin or Nm.

b. MAXIMUM TORQUE _____ lbin or Nm.

3. MISALIGNMENTS *

- a. ANGULAR deg
 b. PARALLEL in. or mm
 c. AXIAL Compression/Extension in. or mm
 d. SKEW – please provide sketch

5. INERTIAL LIMITATION / MASS MOMENT OF INERTIAlb. in. sec² or Kg cm sec²

a. less than _____ b. equal to _____ c. greater than _____

6. WEIGHT

oz. or gm.

a. less than _____ b. equal to _____ c. greater than _____

7. ENVIRONMENT

a. TEMPERATURE _____ °F or °C

b. CORROSIVE _____

c. ABRASIVE _____

FLEXURE AND COMPONENT LAYOUT**8.a.* PREFERRED OUTSIDE DIAMETER** _____ in. or mm

MAXIMUM OUTSIDE DIAMETER _____ in. or mm

c.* DRIVER DESCRIPTION

e.* SHAFT DIAMETER _____ in. or mm**b.* PREFERRED LENGTH** _____ in. or mm

MAXIMUM LENGTH _____ in. or mm

d.* DRIVEN DESCRIPTION

f.* SHAFT DIAMETER _____ in. or mm**9. BORE TOLERANCE****a. COMMERCIAL**

+.002 in. -.000 in.

or

+.05 mm -.00 mm

b. PRECISION

+.0005 in. -.0000 in.

or

+.015 mm -.000 mm

ATTACHMENTS**10. DRIVER*****11. DRIVEN***

a	INTEGRAL CLAMP	a
b	2 SET SCREWS AT 120°	b
c	2 SET SCREWS AT 90°	c
d	1 SET SCREW	d
e	ROLL PIN _____ in. or mm	e
f	DOWEL PIN _____ in. or mm	f
g	KEYWAY _____ type _____ size _____	g
h	OTHER/ DESCRIBE BELOW	h

12. MATERIAL 7075-T6 ALUMINUM ALLOY 17-4 PH STAINLESS STEEL OTHER _____

Type of Equipment _____

Comments _____

* Items marked
with an asterisk
are essential for
optimum design.



Quantity _____

MACHINED SPRINGS BROCHURE


Illustrates pictorially a few of the many applications possible with Helical "machined" springs.



Quantity _____

COUPLING PAMPHLET

12 page pamphlet outlines the steps to choosing or designing the correct Helical coupling.



Quantity _____


ENGINEERING PROPOSAL FORM FOR COMPRESSION SPRINGS



Quantity _____

SPRING PAMPHLET

Information about Helical's Extraordinary "Machined" Springs and the remarkable HELI-CAL® Flexure for your special applications.



Quantity _____

ENGINEERING PROPOSAL FORM FOR TORSION SPRINGS



Quantity _____

DESIGN ENGINEER PAMPHLET

Discusses that your greatest design resource might be the HELI-CAL® Flexure. It make systems work better.



Quantity _____

X-SERIES BULLETIN

Introduces the new, torsionally stiff X-Series coupling, a low cost alternative to bellows types.



Quantity _____

PF SERIES BULLETIN

Presents the many advantages of this innovative power transmission coupling that utilizes the proven HELI-CAL® Flexure.

If interested in receiving any of the above literature, please fill out the information needed, check the appropriate boxes, note the quantities needed and fax to 805-928-2369. If you have any questions please call 805-928-3851. You may also visit our website at <http://www.Heli-Cal.com>.

Name _____ Telephone _____ E-Mail _____

Company _____ Fax _____

Address _____ Street / P.O. Box _____ City _____ State _____ Zip _____



Helical Products Company, Inc. has a unique product in the HELI-CAL Flexure concept. Equally unique and important is the high level of service we at Helical provide to our customers. Together this is our competitive advantage.

When speaking of service we talk of all areas needed to supply the HELI-CAL Flexure to the customer. Putting it in perspective, we like to relate our philosophy to the spokes of a wheel. Each of the spokes represents a unit of our organization - drafting, engineering, finance, administration, shipping, sales, production, manufacturing and marketing. Each in its turn bears the weight of responsibility - and opportunity - to provide and maintain this high level of service to the CUSTOMER - the hub of our wheel.

Passing this commitment on to the next "spoke" requires good, clear communication and cooperation between departments, with the full realization that our focus is always on the customer and their needs. Each department, and, of course, each individual is important at Helical. Helical has never considered itself to be an "I" company, but a "WE" company. With this philosophy we are able to supply an excellent product as well as provide outstanding service at a fair price.

Our commitment has been to build an organization through hard work, fairness, cooperation and mutual trust for each other's roles; to act with courtesy, dependability, reliability, and honesty toward the customer.

Helical does what it says - with pride in its product, its service, and its people. 



The Team



Note: Helical Products Company, Inc., believes the information in this publication is accurate as of its publication date; such information is subject to change without notice.

Helical is not responsible for any inadvertent errors.

The following are trademarks of Helical Products Company, Inc.: HELI-CAL and HELI-CAL Flexure.

WORLD-WIDE PRODUCT SALES OFFICES



"Man's mind, once stretched
by a new idea, never regains its
original dimensions."

- Oliver Wendell Holmes



AS9100B
ISO 9001:2000



Helical Products Company, Inc.

901 W. McCoy Lane, P.O. Box 1069, Santa Maria, CA 93456
Toll Free 877-353-9873, fax 805-928-2369 www.Heli-Cal.com

©Copyright 2008, Helical Products Company, Inc. 080105cat/HJEKTBD